

THE BOATBUILDER'S EPOXY

SYSTEMTHREE

CLEAR COAT EPOXY RESIN

Net Content: lbs.

MIXING:

1. COMBINE THE FOLLOWING PORTIONS:
Two parts BY VOLUME resin to one part BY VOLUME hardener. DO NOT ALTER RATIO. If you mix by weight use hardener at 44 phr.
2. BE SURE TO MIX THOROUGHLY:
Stir from the bottom to the top. Scrape sides occasionally. Larger batches need longer mixing. Use immediately after mixing.

Clear Coat is specifically formulated for boat building and repair. Further information on the use of epoxy resin systems is available in *The Epoxy Book*, published by System Three Resins

NO REPRESENTATIONS OR WARRANTIES OF SUITABILITY OR FITNESS FOR SPECIFIC APPLICATION ARE MADE. PRODUCT SOLD WITHOUT GUARANTEE. SYSTEM THREE RESINS' LIABILITY SHALL BE STRICTLY LIMITED TO REPLACEMENT OF FAULTY MATERIALS AND SHALL NOT BE RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE AS A RESULT OF USING THIS MATERIAL.

WARNING!

MAY CAUSE INJURY TO SKIN OR IRRITATION FOLLOWING PROLONGED OR REPEATED CONTACT. Use in a careful manner with protective clothing to avoid skin contact. MAY CAUSE SKIN SENSITATION. If contact with skin causes irritation, redness, blisters, soreness, swelling, or nausea stop use and contact a physician immediately.

AVOID INHALATION OF FUMES: This product is not to be sprayed. Always be certain you have adequate ventilation when using this material.

AVOID CONTACT WITH EYES: Flush eyes with large quantities of water should contact occur. Contact a physician immediately.

DO NOT TAKE INTERNALLY. DO NOT USE AROUND AN OPEN FLAME.

KEEP OUT OF THE REACH OF CHILDREN

THE BOATBUILDER'S EPOXY

SYSTEMTHREE

CLEAR COAT HARDENER

Net Content: lbs.

MIXING:

3. COMBINE THE FOLLOWING PORTIONS:
Two parts BY VOLUME resin to one part BY VOLUME hardener. DO NOT ALTER RATIO. If you mix by weight use hardener at 44 phr.
4. BE SURE TO MIX THOROUGHLY:
Stir from the bottom to the top. Scrape sides occasionally. Larger batches need longer mixing. Use immediately after mixing.

Clear Coat is specifically formulated for boat building and repair. Further information on the use of epoxy resin systems is available in *The Epoxy Book*, published by System Three Resins

NO REPRESENTATIONS OR WARRANTIES OF SUITABILITY OR FITNESS FOR SPECIFIC APPLICATION ARE MADE. PRODUCT SOLD WITHOUT GUARANTEE. SYSTEM THREE RESINS' LIABILITY SHALL BE STRICTLY LIMITED TO REPLACEMENT OF FAULTY MATERIALS AND SHALL NOT BE RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE AS A RESULT OF USING THIS MATERIAL.

WARNING!

MAY CAUSE INJURY TO SKIN OR IRRITATION FOLLOWING PROLONGED OR REPEATED CONTACT. Use in a careful manner with protective clothing to avoid skin contact. MAY CAUSE SKIN SENSITATION. If contact with skin causes irritation, redness, blisters, soreness, swelling, or nausea stop use and contact a physician immediately.

AVOID INHALATION OF FUMES: This product is not to be sprayed. Always be certain you have adequate ventilation when using this material.

AVOID CONTACT WITH EYES: Flush eyes with large quantities of water should contact occur. Contact a physician immediately.

DO NOT TAKE INTERNALLY. DO NOT USE AROUND AN OPEN FLAME.

KEEP OUT OF THE REACH OF CHILDREN