

MATERIAL SAFETY 3M  
 DATA SHEET 3M Center  
 St. Paul, Minnesota  
 55144-1000  
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.  
 All rights reserved. Copying and/or downloading of this  
 information for the purpose of properly utilizing 3M products  
 is allowed provided that:

- 1) the information is copied in full with no changes unless  
 prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise  
 distributed with the intention of earning a profit thereon.

DIVISION: MARINE TRADES PROJECT  
 TRADE NAME:

3M(TM) Acryl-Marine Putty - White, P.N. 05962, 05963  
 ID NUMBER/U.P.C. :  
 60-9800-0924-9 00-51131-05962-7 60-9800-2096-4 00-51131-05963-4  
 ISSUED: September 24, 2001  
 SUPERSEDES: March 12, 2001  
 DOCUMENT: 10-2849-7

1. INGREDIENT	C.A.S. NO.	PERCENT
TALC.....	14807-96-6	30.0 - 40.0
TITANIUM DIOXIDE.....	13463-67-7	7.0 - 13.0
TOLUENE.....	108-88-3	7.0 - 13.0
N-BUTYL ACETATE.....	123-86-4	5.0 - 10.0
CELLULOSE ACETATE BUTYRATE.....	9004-36-8	5.0 - 10.0
ACRYLIC POLYMER.....	TradeSecret	5.0 - 10.0
XYLENE.....	1330-20-7	5.0 - 10.0
BUTYL BENZYL PHTHALATE.....	85-68-7	1.0 - 5.0
MAGNESIUM CARBONATE.....	546-93-0	1.0 - 5.0
ISOPROPYL ALCOHOL.....	67-63-0	1.0 - 5.0
ETHYLBENZENE.....	100-41-4	1.0 - 5.0
TREATED CLAY.....	71011-26-2	1.0 - 5.0
BENZENE.....	71-43-2	< 0.02

The components of this product are in compliance with the chemical  
 notification requirements of TSCA. All applicable chemical  
 ingredients in this material are listed on the European Inventory of  
 Existing Chemical Substances (EINECS), or are exempt polymers whose  
 monomers are listed on EINECS.

For technical service and product information/support, call  
 1-877-366-2746 (1-877-3M MARINE).

This product contains the following toxic chemical or chemicals subject to  
 the reporting requirements of Section 313 of Title III of the Emergency  
 Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:

TOLUENE  
 XYLENE  
 ETHYLBENZENE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately



-----  
4. REACTIVITY DATA  
-----

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:  
None known.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:  
Carbon Monoxide and Carbon Dioxide, Toxic Vapors, Gases or  
Particulates.

-----  
5. ENVIRONMENTAL INFORMATION  
-----

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Ventilate area. Extinguish all ignition sources. Contain spill. Evacuate unprotected personnel from hazard area. Cover with absorbent material. Cover spill area with Light Water Brand or other AFFF foam. (For further information on AFFF foam usage, contact 3M Fire Protection Systems.) Collect using non-sparking tools. Clean up residue with an appropriate organic solvent. Read and follow safety precautions on the solvent label and MSDS. Place in an approved metal container. Seal the container.

RECOMMENDED DISPOSAL:

Incinerate in a permitted hazardous waste incinerator.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: 424.41 gms/liter calculated per SCAQMD rule 443.1.  
VOC Less H2O & Exempt Solvents: 424.41 gms/liter calculated per SCAQMD rule 443.1.

Since regulations vary, consult applicable regulations or authorities before disposal. In the event of an uncontrolled release of this material, the user should determine if the release qualifies as a reportable quantity. U.S. EPA Hazardous Waste Number = D001 (Ignitable) D018 (Benzene)

EPCRA HAZARD CLASS:

FIRE HAZARD: Yes PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
6. SUGGESTED FIRST AID  
-----

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get medical attention.

INHALATION:

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

-----  
7. PRECAUTIONARY INFORMATION  
-----

EYE PROTECTION:

Avoid eye contact. Wear vented goggles. Wear safety glasses with side shields.

SKIN PROTECTION:

Avoid prolonged or repeated skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended: nitrile rubber, polyethylene/ethylene vinyl alcohol.

RECOMMENDED VENTILATION:

Provide appropriate local exhaust for grinding, cutting or sanding cured material. Use in a well-ventilated area. Provide sufficient ventilation to maintain emissions below recommended exposure limits. If exhaust ventilation is not adequate, use appropriate respiratory protection.

RESPIRATORY PROTECTION:

Avoid breathing of vapors. Avoid breathing of dust created by cutting, sanding or grinding. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half-mask organic vapor respirator with dust/mist prefilter, full-face organic vapor respirator with dust/mist prefilter.

PREVENTION OF ACCIDENTAL INGESTION:

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Wash hands after handling and before eating. Do not ingest.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
 7. PRECAUTIONARY INFORMATION (continued)  
 -----

RECOMMENDED STORAGE:

Store away from heat. Store out of direct sunlight. Keep container closed when not in use. Keep container in well-ventilated area. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed. Keep away from heat, sparks, open flame, and other sources of ignition.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
TALC.....	2	MG/M3	TWA	OSHA	
		RESPIRABLE			
TALC.....	2	MG/M3	TWA	ACGIH	
		RESPIRABLE			
TALC.....	0.5	MG/M3	TWA	CMRG	
		AS RESPIRABLE DUST			
TITANIUM DIOXIDE.....	10	MG/M3	TWA	ACGIH	
TITANIUM DIOXIDE.....	10	MG/M3	TWA	OSHAV	
		AS DUST			
		OSHA VACATED PEL			
TITANIUM DIOXIDE.....	15	MG/M3	TWA	OSHA	
		AS TOTAL DUST			
TITANIUM DIOXIDE.....	5	MG/M3	TWA	CMRG	
		AS RESPIRABLE DUST			
TOLUENE.....	50	PPM	TWA	ACGIH	Y
TOLUENE.....	100	PPM	TWA	OSHAV	
		OSHA VACATED PEL			
TOLUENE.....	150	PPM	STEL	OSHAV	
		OSHA VACATED PEL			
TOLUENE.....	200	PPM	TWA	OSHA	
TOLUENE.....	300	PPM	CEIL	OSHA	
TOLUENE.....	75	PPM	STEL	CMRG	Y
N-BUTYL ACETATE.....	150	PPM	TWA	OSHA	
N-BUTYL ACETATE.....	200	PPM	STEL	OSHA	
N-BUTYL ACETATE.....	150	PPM	TWA	ACGIH	
N-BUTYL ACETATE.....	200	PPM	STEL	ACGIH	
CELLULOSE ACETATE BUTYRATE.....	NONE	NONE	NONE	NONE	
ACRYLIC POLYMER.....	NONE	NONE	NONE	NONE	
XYLENE.....	100	PPM	TWA	ACGIH	
XYLENE.....	150	PPM	STEL	ACGIH	
XYLENE.....	100	PPM	TWA	OSHA	
XYLENE.....	150	PPM	STEL	OSHA	
BUTYL BENZYL PHTHALATE.....	NONE	NONE	NONE	NONE	
MAGNESIUM CARBONATE.....	10	MG/M3	TWA	ACGIH	
MAGNESIUM CARBONATE.....	15	MG/M3	TWA	OSHA	
		AS TOTAL DUST			

-----  
 Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

EXPOSURE LIMITS (continued)

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
MAGNESIUM CARBONATE.....	5	MG/M3	TWA	OSHA	
		RESPIRABLE			
ISOPROPYL ALCOHOL.....	400	PPM	TWA	ACGIH	
ISOPROPYL ALCOHOL.....	500	PPM	STEL	ACGIH	
ISOPROPYL ALCOHOL.....	400	PPM	TWA	OSHA	
ISOPROPYL ALCOHOL.....	500	PPM	STEL	OSHA	
ETHYLBENZENE.....	100	PPM	TWA	ACGIH	
ETHYLBENZENE.....	125	PPM	STEL	ACGIH	
ETHYLBENZENE.....	100	PPM	TWA	OSHA	
ETHYLBENZENE.....	125	PPM	STEL	OSHA	
TREATED CLAY.....	NONE	NONE	NONE	NONE	
BENZENE.....	2.5	PPM	STEL	ACGIH	Y
BENZENE.....	0.5	PPM	TWA	ACGIH	Y
BENZENE.....	1	PPM	TWA	OSHA	
BENZENE.....	5	PPM	STEL	OSHA	
BENZENE.....	0.5	PPM	TWA	OSHA	

OSHA ACTION LEVEL

\* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration
- OSHAV: Occupational Safety and Health Administration Vacated PEL. Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory authority.
- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

SKIN CONTACT:

Moderate Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, itching, and dryness.

May be absorbed through the skin and produce effects similiar to those caused by inhalation and/or ingestion.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
8. HEALTH HAZARD DATA (continued)  
-----

INHALATION:

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system.

Prolonged or repeated overexposure, above recommended guidelines, may cause:

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Prolonged or repeated overexposure, above recommended guidelines, may cause:

Kidney Effects: signs/symptoms can include reduced urine volume, blood in urine and back pain.

Liver Effects: signs/symptoms can include yellow skin(jaundice) and tenderness of upper abdomen.

Central Neuropathy: signs/symptoms can include dizziness, incoordination, visual changes, emotional changes, tremors and convulsions.

Pneumoconiosis (general): signs/symptoms can include persistent coughing and shortness of breath.

IF SWALLOWED:

Ingestion may cause:

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue, blurred vision, slurred speech, giddiness, tremors and convulsions.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
8. HEALTH HAZARD DATA (continued)  
-----

CANCER:

WARNING: Contains a chemical which can cause cancer. (100-41-4) (IARC possible human carcinogen 2B)

WARNING: Contains a chemical which can cause cancer. (71-43-2) (NTP human carcinogen, IARC human carcinogen 1, OSHA listed carcinogen, ACGIH suspected human carcinogen A2, Calif. Proposition 65)

REPRODUCTIVE/DEVELOPMENTAL TOXINS:

WARNING: Contains a chemical which can cause birth defects. (108-88-3)

WARNING: Contains a chemical which can cause birth defects and male reproductive harm. (71-43-2)

WARNING: Contains a chemical which can cause male reproductive harm. (85-68-7)

-----  
SECTION CHANGE DATES  
-----

HEADING	SECTION CHANGED SINCE March 12, 2001	ISSUE
INGREDIENTS	SECTION CHANGED SINCE March 12, 2001	ISSUE
PRECAUTIONARY INFO.	SECTION CHANGED SINCE March 12, 2001	ISSUE
HEALTH HAZARD DATA	SECTION CHANGED SINCE March 12, 2001	ISSUE

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately  
-----

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.