

Carbon Black Pigment

D. O. T. Shipping Name: N/A

EMERGENCY CONTACT NUMBER:

1 (800) 424-9300

Pigment dispersions or concentrates are used to color resin. These pigments are smooth pastes that are quickly and easily dispersed by stirring into liquid resins. Opacity varies with color. Generally opacity is obtained at a pigment level of from one to three percent by weight depending upon color, part thickness and back round.

Pigment should be thoroughly mixed into polyester resin before the addition of the catalyst. If you plan to use more than one batch of colored resin that requires accurate color match it is advisable to mix enough for total requirement and to set aside the extra in a closed can until required.

In epoxies, compatibility test should be made to ascertain the suitability of the pigment due to differences in the types of resins and hardeners. When using in epoxy coatings it is recommended that you limit the pigment level to about two percent.

For urethane systems testing should be done with desired color concentration before use. The pigment should be dispersed into the resin phase.

Store in a cool place in original container not over 75° F.

NET CONTENTS: lbs.

Packaged by:

Fiberglass Supply, Inc.

314 West Depot
Bingen, WA 98605-0345
(509) 493-3464

WARNING: This product contains/produces chemicals known to the state of California to cause cancer, and birth defects or other reproductive harm.

CAUTION: FLAMMABLE LIQUID, CLASS 1C

WARNING: CAUSES EYE IRRITATION-HARMFUL IF INHALED-MAY CAUSE SKIN IRRITATION-HARMFUL IF SWALLOWED-FLAMMABLE.

Avoid contact with eyes and prolonged or repeated contact with skin. Wear goggles and face shield when handling. Avoid breathing of vapor or spray mist. Use only with adequate ventilation. Keep away from heat, spark, and flame.

FIRST AID: in case of contact with skin flush with plenty of water. For eyes immediately flush with plenty of water for 15 minutes and CALL A PHYSICIAN. Wash clothes before re-use. If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth to mouth. If breathing is difficult, give oxygen. If swallowed, CALL A PHYSICIAN IMMEDIATELY. DO NOT induce vomiting.

ATTENTION: THIS CONTAINER IS HAZARDOUS WHEN EMPTIED. Since emptied containers retain product residues (vapor or liquid), all labeled hazard precautions must be observed.

CONSULT MSDS for more complete handling information prior to use.

FOR INDUSTRIAL USE ONLY

HMI S Rating: (**H=1**, **F=0**, **R=0**)

KEEP OUT OF REACH OF CHILDREN