

Styrene Monomer

An Unsaturated Hydrocarbon used in polyester resins as a co-reactant diluent. Used to alter viscosity of polyester resin. Caution should be exercised to not alter resin chemistry. The polymerization of polyester resins is affected by many factors, including Temperature, Mass, Catalysts, Contaminants, and Accelerators. Altering the styrene monomer content of resins can drastically change the final cured physical properties of the resin. Resin manufacturers do not recommend the addition Styrene Monomer without consultation with their technical representatives.

Styrene Monomer is flammable and forms explosive mixtures with air. When styrene is present in concentrations between 1.1% and 6.1%, any source of ignition will set it off. The flash point of styrene is 88° F. Adequate ventilation is recommended. Open flames, local hot-spots, friction and static electricity are to be avoided. Read MSDS before usage.

Store in a cool place in original container not over 75° F.

NET CONTENTS: lbs.

Packaged by: Fiberglass Supply, Inc.
 314 West Depot
 Bingen, WA 98605-0345
 (509) 493-3464

WARNING: This product contains/produces chemicals known to the state of California to cause cancer, and birth defects or other reproductive harm.

D. O. T. Shipping Name:
COATING SOLUTION, 3, UN1139, III, FLAMMABLE LIQUID
CONTAINS: STYRENE MONOMER

EMERGENCY CONTACT NUMBER:

1 (800) 424-9300

CAUTION: FLAMMABLE LIQUID, CLASS 1C

WARNING: CAUSES EYE IRRITATION-HARMFUL IF INHALED-
MAY CAUSE SKIN IRRITATION-HARMFUL IF SWALLOWED-
FLAMMABLE.

Avoid contact with eyes and prolonged or repeated contact with skin. Wear goggles and face shield when handling. Avoid breathing of vapor or spray mist. Use only with adequate ventilation. Keep away from heat, spark, and flame.

FIRST AID: In case of contact with skin, flush with plenty of water. For eyes immediately flush with plenty of water for 15 minutes and CALL A PHYSICIAN. Wash clothes before re-use. If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth to mouth. If breathing is difficult, give oxygen. If swallowed, CALL A PHYSICIAN IMMEDIATELY. DO NOT induce vomiting.

ATTENTION: THIS CONTAINER IS HAZARDOUS WHEN EMPTIED.
Since emptied containers retain product residues (vapor or liquid), all labeled hazard precautions must be observed.

CONSULT MSDS for more complete handling information prior to use.

FOR INDUSTRIAL USE ONLY

HMS Rating: (**H=2**, **F=3**, **R=1**)

KEEP OUT OF REACH OF CHILDREN